

# LED Goldstar™ - D50



A complete range of non-maintained Emergency luminaires for commercial applications.

#### **FEATURES**

- Suitable for all emergency lighting applications
- Energy efficient: less than 1W energy consumption in stand by mode
- Suitable for different hole sizes
- One high Brightness LED
- T-sense<sup>™</sup> temperature sensing technology for LIION battery
- Easy to install spring clips
- Available in black or white finish
- Standalone or MasterMinder emergency monitored
- Manufactured in Australia

### **APPLICATIONS**

- Commercial offices
- Shopping centre
- Facilities
- Public Building applications







Small ring



Medium square

# **TECHNICAL INFORMATION**

■ Operating mode: Maintained

■ Supply voltage: 240V a.c. +/- 6% 50Hz ■ Operating voltage: 0.95W SPU/ 1.4W

■ Battery: NiCd 5 x 1 Sub-C cells linear – 6.0Vdc 1.5Ah

■ IP rating: IP20

■ Body construction: Polycarbonate ■ Operating temperature: 10°C to 40°C

■ Compliance: AS/NZS 2293 AS/NZS 60598



Trim	Dimensions	Hole cut-out		
No Trim	56MM	52MM Ø		
Small ring	80MM	52MM-60MM Ø		
Medium Ring	120MM	52MM-85MM Ø		
Medium square	120x120MM	52MM-85MM Ø		
Wiedium square	120/120101101	JZIVIIVI-OJIVIIVI Ø		

SPU		
Cat No	Description	Classification C0/C90
F9993/LI	LED GOLDSTAR FLEX AND PLUG WHITE LITHIUM	D50
F9993/BL/LI	LED GOLDSTAR FLEX AND PLUG BLACK LITHIUM	D50

MasterMinder		
Cat No	Description	Classification C0/C90
FX9993/LI	LED GOLDSTAR FLEX AND PLUG WHITE LITHIUM	D50
FX9993/BL/LI	LED GOLDSTAR FLEX AND PLUG BLACK LITHIUM	D50

Spacing table: Maximum spacings between luminaires as per AS/NZS 2293

Mounting Height (m)	2.4	2.7	3	3.3	3.6	4.0
A	18.7	19.4	20.1	20.7	21.2	21.8
В	18.7	19.4	20.1	20.7	21.2	21.8




# LED Goldstar™ - D50




### **DIMENSIONS**


## **Fascia**



### **SPU Power Pack**



# **MasterMinder Power Pack**



More info available at:

www.famco.com.au

